

Kootenay Filter

 kootenayfilter.com/product/kfi-1500sl-without-flange/



KFI 1500SL Without Flange

Carbon: Pelletized Activated Carbon CKV-4

Pre-filter installed: Yes

Replacement Pre-filter SKU: PF1500SL

CFM/M3 Ratings:

Max Exhaust CFM – 1260

Max Recirculate CFM – 2520

Max Exhaust M3 – 2100

Max Recirculating M3 – 4200

SKU: SL1500 Category: [Standard Line Filters](#)

| | | |
|---------------------------------------|---|--|
| SKU: | SL1500 | |
| Carbon: | Pelletized Activated Carbon CKV-4 | |
| Flanges Available: | 8" Wide / 10" / 12" / 14" | SKU: FL8W / FL10 / FL12 / FL14 |
| Prefilter Installed: | Yes | |
| Replacement Prefilter SKU: | PF1500SL | |
| Measurements and Weights: | Imperial | Metric |
| Outside Diameter: | 15.8" | 40cm |
| Lengths: | 59.1 | 150cm |
| Total Weight: | 150.0lbs | 68kg |
| Carbon Weight: | 110.2lbs | 50kg |
| Carbon Bed: | 2.55" | 6.5cm |
| Max Operating Temperature: | 176F | 80°C |
| Minimum Recommended Airflow: | 630CFM | |
| Pressure Drop at Max CFM: | 180pa / 0.75"wg | |
| Possible Fan Combinations: | Exhaust | Recirculating |
| | Renegade FR 10 Renegade EC Pro 8 Renegade EC Pro 10 Renegade EC Pro 14 Renegade Silent 10 | Renegade FR 12 Renegade FR 14 Renegade EC Pro 14 Renegade Silent 10 Renegade Silent 12 |

KFI Standard Line filters are made with virgin activated CKV-4 carbon. Each filter is hand made in North America using a proven filing process making this product one of the best filters on the market. At KFI we take pride in our products and ensure our customers receive the highest quality products available.

- Virgin activated, pelletized CKV-4 Carbon
- Dedusted and screened
- Low pressure drop rated @0.1 sec. contact time
- Long service life

- Max operating temperature 80°C / 176°F
- Max allowed humidity 70% (short term only)
- Prefilter installed
- Robust galvanized steel housing
- Single packaged and sealed for storage
- Made in North America
- 2.55" carbon bed
- KFI flanges sold separately, available in 4" to 16"