

Kootenay Filter

 kootenayfilter.com/product/kfi-750-without-flange/



KFI 750 Without Flange

Carbon: Pelletized Activated Carbon CKV-4

Prefilter installed: Yes

Replacement Prefilter SKU: PF750

CFM/M3 Ratings:

Max Exhaust CFM – 600

Max Recirculate CFM – 1200

Max Exhaust M3 – 1000

Max Recirculating M3 – 2000

SKU: SL750 Category: [Standard Line Filters](#)

SKU:	SL750	
Carbon:	Pelletized Activated Carbon CKV-4	
Flanges Available:	6" Wide / 8" Wide/ 10"/ 12"	SKU: FL6W / FL8W / FL10 / FL12
Prefilter Installed:	Yes	
Replacement Prefilter SKU:	FL6W	
Measurements and Weights:	Imperial	Metric
Outside Diameter:	15.8"	40cm
Lengths:	29.5	75cm
Total Weight:	77.0lbs	35kg
Carbon Weight:	55.1lbs	25kg
Carbon Bed:	2.55"	6.5cm
Max Operating Temperature:	176F	80°C
Minimum Recommended Airflow:	300CFM	
Pressure Drop at Max CFM:	180pa / 0.75"wg	
Possible Fan Combinations:	Exhaust	Recirculating
	Renegade FR 8 Renegade EC Pro 8 Renegade Silent 8	Renegade FR 10 Renegade EC Pro 8 Renegade EC Pro 10 Renegade Silent 10 Renegade Silent 12

KFI Standard Line filters are made with virgin activated CKV-4 carbon. Each filter is hand made in North America using a proven filing process making this product one of the best filters on the market. At KFI we take pride in our products and ensure our customers receive the highest quality products available.

- Virgin activated, pelletized CKV-4 Carbon
- Dedusted and screened
- Low pressure drop rated @0.1 sec. contact time
- Long service life

- Max operating temperature 80°C / 176°F
- Max allowed humidity 70% (short term only)
- Prefilter installed
- Robust galvanized steel housing
- Single packaged and sealed for storage
- Made in North America
- 2.55" carbon bed
- KFI flanges sold separately, available in 4" to 16"