

Kootenay Filter

 kootenayfilter.com/product/kfi-330-without-flange/



KFI 330 Without Flange

Carbon: Pelletized Activated Carbon CKV-4

Prefilter installed: Yes

Replacement Prefilter SKU: PF330

CFM/M3 Ratings:

Max Exhaust CFM – 206

Max Recirculate CFM – 412

Max Exhaust M3 – 350

Max Recirculating M3 – 700

SKU: SL330 Category: [Standard Line Filters](#)

SKU:	SL330	
Carbon:	Pelletized Activated Carbon CKV-4	
Flanges Available:	4" Wide / 6" / 8"	SKU: FL4W / FL6 / FL8
Prefilter Installed:	Yes	
Replacement Prefilter SKU:	PF330	
Measurements and Weights:	Imperial	Metric
Outside Diameter:	11.8"	30cm
Lengths:	13.4"	33cm
Total Weight:	24.3lbs	11kg
Carbon Weight:	13.2lbs	6kg
Carbon Bed:	2.0"	5.0cm
Max Operating Temperature:	176F	80°C
Minimum Recommended Airflow:	103CFM	
Pressure Drop at Max CFM:	180pa / 0.75"wg	
Possible Fan Combinations:	Exhaust	Recirculating
	Renegade CF 4 Renegade CF 6 Renegade FR 6 Renegade EC Pro 4 Renegade EC Pro 6	Renegade FR 6 Renegade EC Pro 4 Renegade EC Pro 6

KFI Standard Line filters are made with virgin activated CKV-4 carbon. Each filter is hand made in North America using a proven filing process making this product one of the best filters on the market. At KFI we take pride in our products and ensure our customers receive the highest quality products available.

- Virgin activated, pelletized CKV-4 Carbon
- Dedusted and screened
- Low pressure drop rated @0.1 sec. contact time
- Long service life
- Max operating temperature 80°C / 176°F
- Max allowed humidity 70% (short term only)
- Prefilter installed

- Robust galvanized steel housing
- Single packaged and sealed for storage
- Made in North America
- 2.55" carbon bed
- KFI flanges sold separately, available in 4" to 16"